

GTC-268 Color Dome Camera

KEY FEATURES

- * 1/3" Sony Color HAD CCD / 1/3" Sony Effio-E CCD
- * Horizontal Resolution: 420TV Lines / 650TV Lines
- * Indoor application
- * Digital Signal Processor
- * High Sensitivity Sensor
- * Minimum Illumination 0.08 Lux
- * Power Supply: DC12V±10%
- * Optional Fixed Lens: 3.6, 6, 8, 12mm



TECHNICAL SPECIFICATIONS



Model No	GTC-268-C	GTC-268-G
Image Pick-up Device	1/3" Sony Color HAD CCD	1/3" Sony Effio-E CCD
Total of Pixels No	NTSC: 510(H) x 492(V); PAL: 500(H) x 582(V)	NTSC: 1020(H) x 508(V); PAL: 976(H) x 494(V)
Scanning System	NTSC: 625 Lines, 60fps; PAL: 625 Lines, 50fps	NTSC: 625 Lines, 60fps; PAL: 625 Lines, 50fps
Horizontal Resolution	420TV Lines	650TV Lines
Sync System	Internal Synchronization	Internal Synchronization
S/N Ratio	More than 48dB (AGC Off)	More than 52dB (AGC Off)
Video Output	1.0Vp-p, 75Ω	1.0Vp-p, 75Ω
Electronic Shutter Time	NTSC: 1/60-1/100,000s; PAL: 1/50-1/100,000s	NTSC: 1/60-1/100,000s; PAL: 1/50-1/100,000s
Gamma Characteristic	0.45	0.45
IR Visibility Range	No	No
IR LED	No	No
IR Cut Filter	No	No
Usable Illumination	0.08 Lux (F: 1.2)	0.08 Lux (F: 1.2)
Cable	BNC/DC Jack	BNC/DC Jack
Lens	F: 3.6, 6, 8, 12mm (Optional)	F: 3.6, 6, 8, 12mm (Optional)
White Balance	Auto	Auto
Power Supply	DC12V±10%	DC12V±10%
Dimension	82mm x 116mm	82mm x 116mm
Weight	Approx 200g	Approx 200g

**Design and specifications are subject to change without prior notice.*