

GTC-380-G-WDR IR Dome Camera

KEY FEATURES

- * 1/3" Sony Effio-P CCD
- * Horizontal Resolution: 700TV Lines
- * WideLUX
- * Wide Dynamic Range
- * 2D/3D Noise Reduction (2D/3DNR)
- * Day & Night
- * Highlight Suppression Compensation (HSC)
- * Digital Image Stabilizer [DIS]
- * Varifocal Lens: 4-9mm, 2.8-12mm



TECHNICAL SPECIFICATIONS



Model No	GTC-380-G-WDR
Image Pick-up Device	1/3" Sony Effio-P CCD
Total of Pixels No	NTSC: 1020(H) x 508(V); PAL: 1080(H) x 596(V)
Scanning System	NTSC: 625 Lines, 60fps; PAL: 625 Lines, 50fps
Horizontal Resolution	700TV Lines
Sync System	Internal Synchronization
S/N Ratio	More than 52dB (AGC Off)
Video Output	1.0Vp-p, 75Ω
Electronic Shutter Time	NTSC: 1/60-1/100,000s; PAL: 1/50-1/100,000s
Gamma Characteristic	0.45
IR Visibility Range	40M
IR LED	30pcs
IR Cut Filter	Yes
Color Sensitivity	0.5lux @ F1.2 (50IRE)
Certification	FCC,CE
Wide Dynamic Range	ATR+WDR
OSD Menu	Yes
Lens	V: 4-9mm, 2.8-12mm
Power Supply	DC12V±10%
Dimension	145mm x 124mm
Weight	Approx 850g

**Design and specifications are subject to change without prior notice.*