

GTC-38316-AHD

1.3MP, 16-Channel H.264 with HDMI Analogue High Definition DVR



KEY FEATURES

- *Display Resolution: 720P
- *H.264 video compression algorithm
- *Support 2 SATA hard disk, up to 8TB
- *VGA & HDMI output
- *Continuous/Manual/Motion detect
- *2xUSB(for mouse and backup/upgrade)
- *Multiplex Operation: live display, record, playback, backup and network
- *Network: Lan, DHCP, Dynamic IP and DDNS
- *Video input/output: 16CH inputs / VGA and HDMI output
- *Support Mobile Phones based on iPhone and Android operation system
- *HDD error, HDD full
- *Dimension (mm): 380 x 340 x 50mm

TECHNICAL SPECIFICATIONS



Model		GTC-38316-AHD (720-1.3MP)
Video Compression		H.264
Video System		NTSC/PAL
Operation System		Linux(embedded)
Video-input /output		16CH inputs / VGA and HDMI output
Audio input /output		4CH inputs /1CH output(RCA)
Display	resolution	PAL: 1920*1080P, 1280*720P or 960*480/ NTSC: 1920*1080P, 1280*720P or 960*576
	feature	single/ Quad/Nine/Sixteen/S.E.Q., on phone, CMS, IE or PC
Record	resolution	PAL: 1920*1080P,1280*720P or 960*480/ NTSC: 1920*1080P,1280*720P or 960*576
	speed	PAL:15-25fps (each chn) @720p or 25fps(each ch) @960H NTSC: 15-25fps (each chn) @720p or 30fps(each chn) @960H
Recording Mode		Continuous/Manual/Motion detect
Playback Channel	Local	1~16ch
	PC & Mac	1~4ch
	Mobile	1ch (Using App: GTC Camviewer)
Playback speed (Simultaneously Record)		PAL:25fps (One chn) or 15fps (mutiple chn) @720p or 25fps(each chn) @960H NTSC: 25fps (One chn) or 15fps (mutiple chn) @720p or 30fps(each chn) @960H
Sensor & Alarm I/O		4 inputs /1 output
Network Type		Lan, DHCP, Dynamic IP and DDNS
E-mail Notifications		Support
HDD interface		2 SATA HDDs, up to 8TB
Multiplex Operation		live display, record, playback, backup and network
USB		2xUSB(for mouse and backup/upgrade)
PTZ Control		Yes
Mobile Surveillance		Support Mobile Phones based on iPhone and Android operation system
VGA		800*600,1024*768,1280*1024,1440*900,1920*1080
HDMI		1080P
IR Extender Port		Optional
CLOUD		Support
P2P		Support
Power Supply		DC 12V/2A
Dimension(WxDxH)		380x340x50mm

**Design and specifications are subject to change without prior notice.*